

ÖLFLEX® PETRO C HFFR multicore**DB 0023252**
valid from: 19.12.2017**Application**

ÖLFLEX® PETRO C HFFR - multi core is designed as connection and control cable especially for offshore applications like for instance on oil rigs for the cabling of pumping stations, compressors and generators of drilling units. The cable is UV-, oil-, MUD- and abrasion resistant for the use in harsh environment. The selected insulation and outer sheath compounds are halogen free and flame retardant resp. self-extinguishing. The tinned copper braiding serves as screening against electrical interference. Depending on normative interpretation the braiding also can be used as so-called „Braid Armour“.

Use acc. to RU: PUR sheathed cable for external interconnection of electronic equipment.

Use acc. to cRU: PUR sheathed cable for external interconnection of electronic equipment with or without mechanical load conditions.

Design

Design	according to UL AWM 20234 based on DIN EN 50525-3-11 resp. VDE 0285-525-3-11
Approval	UL AWM 758, Style 20234 (File No. E63634) cRU AWM II A/B, (File No. E63634)
Conductor	fine wire strands of tinned copper acc. to IEC 60228 resp. VDE 0295, Class 5
Core insulation	polyolefine compound, halogen free
Core identification	acc. to VDE 0293-1, with or without GN/YE protective conductor up to 5 cores: coloured acc. to VDE 0293-308 resp. HD 308 S2 starting at 6 cores: black cores with white numbers acc. to DIN EN 50334 resp. VDE 0293-334
Stranding	cores twisted together into layers
Taping	non-woven wrapping
Inner sheath	halogen free special compound, colour black
Screen	braid of tinned copper wires, coverage = 85% (nominal value)
Outer sheath	special polymer compound, oil resistant, halogen free and flame retardant colour : black, similar RAL 9005 or blue, similar RAL 5015

Electrical properties

Nominal voltage	U ₀ /U: 600/1000 V RU/cRU: 1000 V
Test voltage	Core/Core: 4000 V AC Core/Screen: 4000 V AC

Mechanical and thermal properties

Min. bending radius	occasional flexing: 20 x cable diameter fixed installation: 6 x cable diameter
Temperature range	occasional flexing: -40 °C up to +90 °C max. conductor temp. occasional flexing (RU/cRU): up to +80 °C max. conductor temp. fixed installation: -50 °C up to +90 °C max. conductor temp. fixed installation(RU/cRU): up to +80 °C max. conductor temp.

ÖLFLEX® PETRO C HFFR multicore

DB 0023252
valid from: 19.12.2017

Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2 RU: Vertical flame test VW-1 cRU: FT1 flame propagation acc. to IEC 60332-3-22 resp. EN 60332-3-22 test, cat. A
Oil resistance	acc. to EN 50363-10-2- resp. VDE 0207-363-10-2 and NEK TS 606: 2016
MUD resistance	acc. to NEK TS 606:2016 and IEC 61892-4, Annex D
Salt water resistance	acc. to UL 1309
Halogen-free	acc. to VDE 0472-815
UV-resistance	acc. to VDE 0276-605 EN ISO 4892-2, method A (change of colour allowed)
Ozone resistance	acc. to EN 50396 resp. VDE 0473-396 method B
Tests	acc. to IEC 60811 resp. VDE 0473 part 811, EN 50395, EN 50396, UL 1581 und CSA C22.2
EU Directive	These cables are conform to the EU-Directives 2014/35/EU (Low Voltage Directive).